neutrakon®

neutralisiert saure Kondensate



Neutrakon Pro SN90 April 2021







Neutrakon Professional SN90



Neutrakon Professional SN90









Background





Neutrakon Pro SN90 – A scalable and thought through solution for treating big amounts of exhaust and condensing boiler condensates in a clean, easy and problem-free manner, thus making a strong contribution to water and water systems protection!

Internal market research showed a clear lack of a solution in this segment. There are some specific projects with special solutions, but none with a "system".

This protected utility model is a milestone in the handling of condensates from large systems. The complete product as well as the baskets are registered as "DBGM" (Deutsches Bundes-Gebrauchsmuster) in the German Patent and Trademark Office (Deutschen Patent- und Markenamt).

Final prototyping February 2021:













Neutrakon Pro SN90

The new neutralisation unit Neutrakon Pro SN90 is made of high quality stainless steel with a lenght of approx. 110cm, a width of approx. 35cm and a height of approx. 40 cm.

Appropriated for acidic condensates deriving from exhaust and condensing boilers, CHP or chimneys up to 11 MW or 1500 l/h, it convices right away with its compact design and the innovative neutralising baskets. High quality stainless steel (V4A) assures acidic and temperature resistance, and fits optically in every professional environment, regardless of inner or outside usage.

Neutrakon Pro SN90 - baskets









Neutralising baskets- optimal condensate flow

The Neutrakon Pro SN90 has 3 juxtaposed neutralisation baskets to ensure an easy handling for carrying out maintenance works.

Through ist possible scalability an individualization of the neutralisation capacity is possible. The sequence of the baskets was not left to chance. Guided by the separation partition on the intake side, the condensate is directed immediately the right way when entering the neutralisation box. Through the lenght of the Neutrakon Pro SN 90 and the condensate flowing, sufficient contact time with the neutralising agent is ensured. The number of baskets can be adapted to the specific needs.

Maintenance

Through the intelligent, but easy lock and release function of the baskets an uncomplicated carrying out of maintenance works is possible, even for this size of unit. Each basket can be removed from the neutralisation box Neutrakon Pro SN90 by pushing the basket on the left and right side levers. The granules can then be exchanged and/or cleaned in ist entirety. A ball valve allows full drainage of the neutralisation box.



Detail neutralising baskets



Condensate intake pipes and ball valve for maintenance works



Condensate outlet pipe



General perspective





Detail from inside condensate intake pipes with partition wall



Stainless steel box without baskets



Condensate outlet pipe with basket locking function



General perspective







Technical Data Neutrakon Pro SN90



<u>Technical Data</u>	
Suitable for	acidic condensates deriving from exhaust and condensing boilers, CHP or chimneys
Output	11MW
Max. condensate volume flow (0,08l/kwH)	1500
Execution	Stainless steel V4A
Weight stainless steel box	25kg
Weight stainless steel cover	7,5 kg
Weight neutralising baskets	7kg
Total weight (stainless steel box, stainless steel cover, 3 neutralising baskets)	53,5kg
Granules filling quantity (per basket)	30kg (max.)
Dimensions (w/o fittings)	lenght 1137 mm; width 350mm; height 402mm
Dimensions (with fittings)	lenght 1185 mm; width 450 mm; height 402mm
Amount neutralising baskets	3
Intake (2x)	1 1/4"
Outlet (1x)	1 1/2"
Height (intake/Outlet)	125mm; 210mm
Ball valve	1"
Mommertz part number	097000



Neutrakon Pro SN90 – mounting example









